

1 **Amendment to the Specification**

2 **In the Specification:**

3 Please amend the specification as follows:

4 *On Page ¹⁴ 3 of the published application, paragraph 0023 should be replaced with the*
 5 *following.*

6 Other embodiments of the present invention relate to integrated systems, which include the impact
 7 collection surface as well. It is anticipated that the present invention will perform particularly effectively if
 8 fluid-entrained particulates (most often airborne particulates) are efficiently collected and concentrated, a task
 9 for which a virtual impactor, such as described in a commonly owned copending U.S. Patent Application Ser.
 10 No. [[____]] 10/066,404 (issued on May 3, 2005 as U.S. Patent No. 6,887,710) entitled "ROBUST
 11 SYSTEM FOR SCREENING MAIL FOR BIOLOGICAL AGENTS." It is also particularly useful to
 12 providing means for moving the collection surface relative to the concentrated stream of particulates over time,
 13 so that spots located on different portions of the surface correspond to specific different increments of time.
 14 Preferably, the individual spots are disposed sufficiently far apart such that each individual spot can be
 15 removed and transferred to a suitable container without disturbing other spots.

16 *On Page ³⁰ 8 of the published application, paragraph 0098 should be replaced with the*
 17 *following.*

18 FIG. 26 is a diagram of several components present in various embodiments of the present invention,
 19 namely an impaction plate ~~(2605)~~ (205) with a collection surface on which a deposit (220) forms ~~(2620)~~, a
 20 spotting nozzle ~~(2610)~~ (210), an analyzer comprising a fluorescence photosensor ~~(2630)~~ (230) and an
 21 excitation light source ~~(2640)~~ (240) coupled by wires ~~(2650)~~ (250), a shaft ~~(2660)~~ (260) mounted to the
 22 impaction plate ~~(2605)~~ (205) by a bracket ~~(2670)~~ (270) and a regenerator ~~(2680)~~ (280). Three collection
 23 surfaces/spots (220) are drawn only for illustration; a single collection surface suffices in most embodiments;

24 *On Page ¹⁵⁸ 30 of the published application, paragraph 0316 should be replaced with the*
 25 *following.*

26 In one embodiment the excitation light source (240) is positioned underneath a horizontal UV
 27 transparent impact plate (205), and the emission sensor (fluorescence photosensor 230) is positioned
 28 above the plate, as is the collection surface (see ~~FIG. 2~~ FIG. 26). For example, the impaction plate
 29 (205) may be shaped as a disk or may otherwise be planar. Accordingly, the impaction plate (205) has
 30 a collection surface side, on which the spot (220) forms, and a side opposite to the collection surface